

Wall mounted receptacle  
Part no. 7136




- screw terminals
- fused with fuse socket D 01 or D 02

Technical specifications

|                       |                 |
|-----------------------|-----------------|
| Ampere                | 32 A            |
| Poles                 | 5 p             |
| Voltage               | 400 V           |
| Clock position        | 6 h             |
| Hertz                 | 50-60 Hz        |
| Connection technology | Screw terminals |
| Contact               | standard        |
| Protection type       | IP 67           |
| Enclosure material    | Plastic         |
| Weight                | 1461 g          |

Drawing



| Drawing<br>1 MB 378                                 | Amp.<br>Poles | 16            |      |      | 32            |      |
|-----------------------------------------------------|---------------|---------------|------|------|---------------|------|
|                                                     |               | 3             | 4    | 5    | 4             | 5    |
| Dim. in mm                                          |               |               |      |      |               |      |
| a                                                   |               | 225           | 225  | 225  | 225           | 225  |
| b                                                   |               | 118           | 118  | 118  | 118           | 118  |
| c                                                   |               | 144           | 146  | 147  | 152           | 153  |
| d                                                   |               | 208           | 208  | 208  | 208           | 208  |
| e                                                   |               | 101           | 101  | 101  | 101           | 101  |
| f                                                   |               | 6.3           | 6.3  | 6.3  | 6.3           | 6.3  |
| g                                                   |               | 8             | 8    | 8    | 8             | 8    |
| h                                                   |               | 252           | 255  | 259  | 268           | 274  |
| M                                                   |               | 1x25 and 1x32 |      |      | 1x25 and 1x32 |      |
| M*                                                  |               | 2x25          | 2x25 | 2x25 | 2x25          | 2x25 |
| Max. cable diam. (mm)                               |               | 25            | 25   | 25   | 25            | 25   |
| Terminal for cond. cross<br>section (mm²) min.-max. |               | 1.5           | 1.5  | 1.5  | 2.5           | 2.5  |
|                                                     |               | —4            | —4   | —4   | —10           | —10  |