

Wall mounted receptacle  
Part no. 7285




- screw terminals
- highly resistant to chemicals
- highly heat resistant contact carrier
- nickel plated contacts
- switched
- mechanical DUO-interlock
- receptacles can be padlocked

Technical specifications

|                           |                                                               |
|---------------------------|---------------------------------------------------------------|
| Ampere                    | 16 A                                                          |
| Poles                     | 5 p                                                           |
| Voltage                   | 400 V                                                         |
| Clock position            | 6 h                                                           |
| Hertz                     | 50-60 Hz                                                      |
| Connection technology     | Screw terminals                                               |
| Contact                   | nickel plated contacts, highly heat resistant contact carrier |
| Protection type           | IP 67                                                         |
| Enclosure material        | Plastic, high resistance to chemicals                         |
| Weight                    | 1195 g                                                        |
| Declaration of Conformity | DE,VDE, CN,CQC                                                |

Drawing



| Drawing<br>1 MB 207      | Amp.<br>Poles | 16              |      |      | 32              |      |      |
|--------------------------|---------------|-----------------|------|------|-----------------|------|------|
|                          |               | 3               | 4    | 5    | 3               | 4    | 5    |
| Dim. in mm               | a             | 225             | 225  | 225  | 225             | 225  | 225  |
|                          | b             | 118             | 118  | 118  | 118             | 118  | 118  |
|                          | c             | 144             | 146  | 147  | 152             | 152  | 153  |
|                          | d             | 208             | 208  | 208  | 208             | 208  | 208  |
|                          | e             | 101             | 101  | 101  | 101             | 101  | 101  |
|                          | f             | 6.3             | 6.3  | 6.3  | 6.3             | 6.3  | 6.3  |
|                          | g             | 8               | 8    | 8    | 8               | 8    | 8    |
|                          | h             | 252             | 255  | 259  | 268             | 268  | 274  |
|                          | M             | 1xM25 and 1xM32 |      |      | 1xM25 and 1xM32 |      |      |
|                          | M*            | 2x25            | 2x25 | 2x25 | 2x25            | 2x25 | 2x25 |
| Max. cable diam. (mm)    |               | 25              | 25   | 25   | 25              | 25   | 25   |
| Terminal for cond. cross |               | 1.5             | 1.5  | 1.5  | 2.5             | 2.5  | 2.5  |
| section (mm²) min.-max.  |               | —4              | —4   | —4   | —10             | —10  | —10  |