

AMAXX® receptacle combination
Part no. 920003




- pre-wired for installation
- hinged to the side
- enclosure and insert made of AMAPLAST
- fusing behind a transparent cover

Technical specifications

SCHUKO® 16 A, 230 V	3
Fusing	• 1 RCD 40 A, 4 p, 0.03 A • 3 MCB's 16 A, 1 p, C
Pre-fuse max.	100 A
InA	16 A
RDF	1
Connection / feeder cable	• for 1 cable up to 5 x 10 mm²
Protection type	IP 44
Enclosure material	Plastic
Weight	2940 g
Height	260 mm
Width	225 mm

Drawing



Drawing 1 MB 521

Depth dimensions at various fittings.

Receptacles	Degrees	Depth
SCHUKO® 16A, 230 V	IP 44	175 mm
	IP 67	194 mm
CEE 16A, 3p, 230V	IP 44	204 mm
	IP 67	205 mm
CEE 16A, 5p, 400V	IP 44	209 mm
	IP 67	213 mm
CEE 32A, 5p, 400V	IP 44	221 mm
	IP 67	227 mm
CEE 63A, 5p, 400V	IP 44	248 mm
	IP 67	248 mm

Cable entries: closed for cut out. 2 x M 32 each on top and bottom, 2 x M 20 each on top and bottom for cut out.