

Wall mounted receptacle  
Part no. 9510




- screw terminals
- highly resistant to chemicals
- highly heat resistant contact carrier
- nickel plated contacts
- two external fixing points
- receptacles are designed for adding an auxiliary contact switch
- enclosure base can be turned 180°

Technical specifications

|                           |                                                               |
|---------------------------|---------------------------------------------------------------|
| Ampere                    | 16 A                                                          |
| Poles                     | 4 p                                                           |
| Voltage                   | 400 V                                                         |
| Clock position            | 6 h                                                           |
| Hertz                     | 50-60 Hz                                                      |
| Connection technology     | Screw terminals                                               |
| Contact                   | highly heat resistant contact carrier, nickel plated contacts |
| Protection type           | IP 67                                                         |
| Weight                    | 385 g                                                         |
| Declaration of Conformity | CN,CQC                                                        |

Drawing



|                                                  |       |                            |      |      |                            |      |      |
|--------------------------------------------------|-------|----------------------------|------|------|----------------------------|------|------|
| Drawing                                          | Amp.  | 16                         |      |      | 32                         |      |      |
| 1 MB 622                                         | Poles | 3                          | 4    | 5    | 3                          | 4    | 5    |
| Dim. in mm                                       | a     | 100                        | 100  | 100  | 100                        | 100  | 100  |
|                                                  | b     | 101                        | 101  | 101  | 109                        | 109  | 109  |
|                                                  | c     | 117                        | 125  | 131  | 157                        | 157  | 160  |
|                                                  | d     | 50                         | 50   | 50   | 50                         | 50   | 50   |
|                                                  | e     | 84                         | 84   | 84   | 92                         | 92   | 92   |
|                                                  | f1    | 5.3                        | 5.3  | 5.3  | 5.3                        | 5.3  | 5.3  |
|                                                  | f2    | 5.3                        | 5.3  | 5.3  | 5.3                        | 5.3  | 5.3  |
|                                                  | g     | 6.5                        | 6.5  | 6.5  | 6.5                        | 6.5  | 6.5  |
|                                                  | h     | 131                        | 131  | 132  | 148                        | 148  | 148  |
|                                                  | i     | 24.7                       | 24.7 | 24.7 | 27.5                       | 27.5 | 27.5 |
|                                                  | M     | 25 (optional M20)          |      |      | 32 (optional M25)          |      |      |
|                                                  | M*    | 2x25 (blind) to be cut out |      |      | 2x25 (blind) to be cut out |      |      |
| Max. cable diam. (mm)                            |       | 18 (M25) and 15 (M20)      |      |      | 25 (M32) and 18 (M25)      |      |      |
| Terminal for cond. cross section (mm²) min.-max. |       | 1.5                        | 1.5  | 1.5  | 2.5                        | 2.5  | 2.5  |
|                                                  |       | —4                         | —4   | —4   | —6                         | —6   | —6   |