

Wall mounted receptacle  
Part no. 3035




- screw terminals
- internal fixing
- one cable entry at top, two blind cable entries (can be cut out) at bottom
- enclosure base can be turned 180°
- receptacles are designed for adding an auxiliary contact switch

Technical specifications

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 16 A            |
| Poles                     | 4 p             |
| Voltage                   | 50-500 V        |
| Clock position            | 10 h            |
| Hertz                     | 100-300 Hz      |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Weight                    | 293 g           |
| Declaration of Conformity | CN,CQC          |

Drawing



| Drawing<br>1 MB 43                               | Amp.<br>Poles | 16                         |     | 32                         |       |       |
|--------------------------------------------------|---------------|----------------------------|-----|----------------------------|-------|-------|
|                                                  |               | 4                          | 5   | 3                          | 4     | 5     |
| Dim. in mm                                       | a             | 128                        | 128 | 128                        | 128   | 128   |
|                                                  | b             | 84                         | 84  | 84                         | 84    | 84    |
|                                                  | c             | 122                        | 124 | 136                        | 136   | 138   |
|                                                  | d             | 11                         | 11  | 11                         | 11    | 11    |
|                                                  | e             | 68                         | 68  | 68                         | 68    | 68    |
|                                                  | f             | 5.3                        | 5.3 | 5.3                        | 5.3   | 5.3   |
|                                                  | g             | 4                          | 4   | 4                          | 4     | 4     |
|                                                  | h             | 144                        | 145 | 158                        | 158   | 160   |
|                                                  | M             | 25                         | 25  | 32                         | 32    | 32    |
|                                                  | M*            | 2x25 (blind) to be cut out |     | 2x25 (blind) to be cut out |       |       |
| Max. cable diam. (mm)                            |               | 18                         | 18  | 18/25                      | 18/25 | 18/25 |
| Terminal for cond. cross section (mm²) min.-max. |               | 1.5                        | 1.5 | 2.5                        | 2.5   | 2.5   |
|                                                  |               | —4                         | —4  | —10                        | —10   | —10   |