

Wall mounted receptacle
Part no. 3141




- screw terminals
- internal fixing
- one cable entry at top and two blind cable entries (can be cut out) at bottom
- enclosure base can be turned 180°

Technical specifications

Ampere	32 A
Poles	3 p
Voltage	Isolating transformer
Clock position	12 h
Connection technology	Screw terminals
Contact	standard
Protection type	IP 44
Weight	355 g
Declaration of Conformity	DE,VDE, CN,CQC

Drawing



Drawing 1 MB 43 Dim. in mm	Amp. Poles	16		32		
		4	5	3	4	5
a		128	128	128	128	128
b		84	84	84	84	84
c		122	124	136	136	138
d		11	11	11	11	11
e		68	68	68	68	68
f		5.3	5.3	5.3	5.3	5.3
g		4	4	4	4	4
h		144	145	158	158	160
M		25	25	32	32	32
M*		2x25 (blind) to be cut out		2x25 (blind) to be cut out		
Max. cable diam. (mm)		18	18	18/25	18/25	18/25
Terminal for cond. cross section (mm²) min.-max.		1.5 1.5	1.5 1.5	2.5 2.5	2.5 2.5	2.5 2.5
		—4 —4	—4 —4	—10 —10	—10 —10	—10 —10