

Wall mounted receptacle
Part no. 7296




- screw terminals
- X-CONTACT®
- highly resistant to chemicals
- highly heat resistant contact carrier
- nickel plated contacts
- switched
- mechanical DUO-interlock
- DIN-rail
- receptacles can be padlocked

Technical specifications

Ampere	63 A
Poles	5 p
Voltage	400 V
Clock position	6 h
Hertz	50-60 Hz
Connection technology	Screw terminals
Contact	X-CONTACT®
Protection type	IP 67
Enclosure material	Plastic, high resistance to chemicals
Weight	4338 g
Declaration of Conformity	CN,CQC

Drawing



Drawing	Amp.	16			32		63		
		Poles			Poles		Poles		
1 MB 181/620		3	4	5	4	5	4	5	
Dim. in mm									
a		364	364	364	364	364	460	460	
b		134	134	134	134	134	180	180	
c		160	162	163	168	168	202	202	
d		347	347	347	347	347	440	440	
e		117	117	117	117	117	160	160	
f		6.3	6.3	6.3	6.3	6.3	8.1	8.1	
g		8	8	8	8	8	8	8	
h		391	395	398	408	411	505	505	
M		32/40	32/40	32/40	32/40	32/40	40	40	
M*		2x32	2x32	2x32	2x32	2x32	2x40	2x40	
Max. cable diam. (mm)		27	27	27	27	27	27	27	
Terminal for cond. cross		1.5	1.5	1.5	2.5	2.5	6	6	
section (mm²) min.-max.		—4	—4	—4	—10	—10	—25	—25	