

Wall mounted receptacle  
Part no. 9327




- screw terminals
- highly resistant to chemicals
- with 2 external fixing points
- receptacles are designed for adding an auxiliary contact switch
- enclosure can be turned 180°

Technical specifications

|                       |                       |
|-----------------------|-----------------------|
| Ampere                | 16 A                  |
| Poles                 | 4 p                   |
| Voltage               | Isolating transformer |
| Clock position        | 12 h                  |
| Connection technology | Screw terminals       |
| Contact               | standard              |
| Protection type       | IP 67                 |
| Weight                | 378 g                 |

Drawing



| Drawing<br>1 MB 622                              | Amp.<br>Poles | 16                         |      |      | 32                         |      |      |
|--------------------------------------------------|---------------|----------------------------|------|------|----------------------------|------|------|
|                                                  |               | 3                          | 4    | 5    | 3                          | 4    | 5    |
| Dim. in mm                                       | a             | 100                        | 100  | 100  | 100                        | 100  | 100  |
|                                                  | b             | 101                        | 101  | 101  | 109                        | 109  | 109  |
|                                                  | c             | 117                        | 125  | 131  | 157                        | 157  | 160  |
|                                                  | d             | 50                         | 50   | 50   | 50                         | 50   | 50   |
|                                                  | e             | 84                         | 84   | 84   | 92                         | 92   | 92   |
|                                                  | f1            | 5.3                        | 5.3  | 5.3  | 5.3                        | 5.3  | 5.3  |
|                                                  | f2            | 5.3                        | 5.3  | 5.3  | 5.3                        | 5.3  | 5.3  |
|                                                  | g             | 6.5                        | 6.5  | 6.5  | 6.5                        | 6.5  | 6.5  |
|                                                  | h             | 131                        | 131  | 132  | 148                        | 148  | 148  |
|                                                  | i             | 24.7                       | 24.7 | 24.7 | 27.5                       | 27.5 | 27.5 |
|                                                  | M             | 25 (optional M20)          |      |      | 32 (optional M25)          |      |      |
|                                                  | M*            | 2x25 (blind) to be cut out |      |      | 2x25 (blind) to be cut out |      |      |
|                                                  |               | 18 (M25) and 15 (M20)      |      |      | 25 (M32) and 18 (M25)      |      |      |
| Max. cable diam. (mm)                            |               | 1.5                        | 1.5  | 1.5  | 2.5                        | 2.5  | 2.5  |
| Terminal for cond. cross section (mm²) min.-max. |               | —4                         | —4   | —4   | —6                         | —6   | —6   |