


**Panel mounted receptacle**  
Part no. 1250A




- screw terminals
- X-CONTACT®
- straight
- products with pilot contact on request

**Technical specifications**

|                           |                                          |
|---------------------------|------------------------------------------|
| Ampere                    | 63 A                                     |
| Poles                     | 5 p                                      |
| Voltage                   | 110 V                                    |
| Clock position            | 4 h                                      |
| Hertz                     | 50-60 Hz                                 |
| Connection technology     | Screw terminals                          |
| Contact                   | X-CONTACT®                               |
| Protection type           | IP 44                                    |
| Shutter                   | false                                    |
| Flange                    | 107x100 mm                               |
| Fixing hole               | 85x77 mm                                 |
| Weight                    | 620 g                                    |
| Declaration of Conformity | DE,VDE, RU,EAC (Zwangszulassung), CN,CQC |

**Drawing**



|                          |       |     |     |     |
|--------------------------|-------|-----|-----|-----|
| Drawing                  | Amp.  | 63  |     |     |
| 1 MB 211                 | Poles | 3   | 4   | 5   |
| Dim. in mm               | a     | 107 | 107 | 107 |
|                          | b     | 100 | 100 | 100 |
|                          | c     | 80  | 80  | 80  |
|                          | d     | 85  | 85  | 85  |
|                          | e     | 77  | 77  | 77  |
|                          | f     | 6   | 6   | 6   |
|                          | g.    | 12  | 12  | 12  |
|                          | g.1   | 2   | 2   | 2   |
|                          | h     | 113 | 113 | 113 |
|                          | k     | 55  | 55  | 55  |
|                          | l     | 88  | 88  | 88  |
| Terminal for cond. cross |       | 6   | 6   | 6   |
| section (mm²) min.-max.  |       | —25 | —25 | —25 |