

**Plug PowerTOP® Xtra**  
Part no. 13238




- screw terminals
- rubberised grip area
- frame terminals
- highly heat resistant contact carrier
- nickel plated contacts
- cable gland and sealing
- strain relief and protection against kinking
- enclosure with thread lock
- two safety slides

Technical specifications

|                       |                                                               |
|-----------------------|---------------------------------------------------------------|
| Ampere                | 125 A                                                         |
| Poles                 | 4 p                                                           |
| Voltage               | 600-690 V                                                     |
| Clock position        | 5 h                                                           |
| Hertz                 | 50-60 Hz                                                      |
| Connection technology | Screw terminals                                               |
| Contact               | highly heat resistant contact carrier, nickel plated contacts |
| Protection type       | IP 67                                                         |
| Weight                | 1400 g                                                        |

Drawing



| Drawing<br>2 MB 225      | Amp.<br>Poles | 63  |     |     | 125 |     |     |
|--------------------------|---------------|-----|-----|-----|-----|-----|-----|
|                          |               | 3   | 4   | 5   | 3   | 4   | 5   |
| Dim. in mm               | a             | 250 | 250 | 250 | 290 | 290 | 290 |
|                          | b             | 114 | 114 | 114 | 130 | 130 | 130 |
|                          | y             | 36  | 36  | 36  | 49  | 49  | 49  |
| Terminal for cond. cross |               | 6   | 6   | 6   | 25  | 25  | 25  |
| section (mm²) min.-max.  |               | —16 | —16 | —16 | —50 | —50 | —50 |