

Panel mounted receptacle with TwinCONTACT  
Part no. 1807




- screwless spring terminals
- suitable for through wiring
- 20° inclination
- receptacles are designed for adding an auxiliary contact switch

Technical specifications

|                           |                         |
|---------------------------|-------------------------|
| Ampere                    | 32 A                    |
| Poles                     | 4 p                     |
| Voltage                   | 50-500 V                |
| Clock position            | 10 h                    |
| Hertz                     | 100-300 Hz              |
| Connection technology     | Screwless - TwinCONTACT |
| Contact                   | standard                |
| Protection type           | IP 67                   |
| Flange                    | 100x92 mm               |
| Fixing hole               | 85x77 mm                |
| Inclination               | 20 °                    |
| Weight                    | 273 g                   |
| Declaration of Conformity | DE,VDE                  |

Drawing



| Drawing<br>1 MB 466 | Amp.<br>Poles            | 16   |     |     | 32  |     |     |
|---------------------|--------------------------|------|-----|-----|-----|-----|-----|
|                     |                          | 3    | 4   | 5   | 3   | 4   | 5   |
| Dim. in mm          | a                        | 73.5 | 100 | 100 | 100 | 100 | 100 |
|                     | b                        | 64   | 92  | 92  | 92  | 92  | 92  |
|                     | c                        | 52   | 60  | 62  | 66  | 66  | 66  |
|                     | d                        | 60   | 85  | 85  | 85  | 85  | 85  |
|                     | e                        | 52   | 77  | 77  | 77  | 77  | 77  |
|                     | f                        | 5.5  | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 |
|                     | g                        | 7    | 8   | 8   | 8   | 8   | 8   |
|                     | g.1                      | 2    | 2   | 2   | 2   | 2   | 2   |
|                     | h                        | 84   | 100 | 106 | 109 | 109 | 113 |
|                     | k                        | 31   | 31  | 31  | 44  | 44  | 54  |
|                     | l                        | 52   | 55  | 65  | 70  | 70  | 73  |
|                     | l1                       | 60   | 63  | 72  | 82  | 82  | 85  |
|                     | Terminal for cond. cross | 1.5  | 1.5 | 1.5 | 2.5 | 2.5 | 2.5 |
|                     | section (mm²) min.-max.  | —4   | —4  | —4  | —6  | —6  | —6  |