

Panel mounted receptacle  
Part no. 1819




- screwless
- with TwinCONTACT
- flange: 16 A: 75 x 75 mm, 32 A: 85 x 75 mm
- straight

Technical specifications

|                           |                         |
|---------------------------|-------------------------|
| Ampere                    | 32 A                    |
| Poles                     | 5 p                     |
| Voltage                   | 230 V                   |
| Clock position            | 9 h                     |
| Hertz                     | 50-60 Hz                |
| Connection technology     | Screwless - TwinCONTACT |
| Contact                   | standard                |
| Protection type           | IP 67                   |
| Flange                    | 85x75 mm                |
| Fixing hole               | 60x60 mm                |
| Weight                    | 120 g                   |
| Declaration of Conformity | DE,VDE                  |

Drawing



| Drawing<br>1 MB 467 | Amp.<br>Poles                                       | 16          |             |             | 32          |             |             |
|---------------------|-----------------------------------------------------|-------------|-------------|-------------|-------------|-------------|-------------|
|                     |                                                     | 3           | 4           | 5           | 3           | 4           | 5           |
| Dim. in mm          | a                                                   | 75          | 75          | 75          | 85          | 85          | 85          |
|                     | b                                                   | 75          | 75          | 75          | 75          | 75          | 75          |
|                     | c                                                   | 60          | 61          | 61          | 69          | 69          | 72          |
|                     | d                                                   | 60          | 60          | 60          | 60          | 60          | 60          |
|                     | e                                                   | 60          | 60          | 60          | 60          | 60          | 60          |
|                     | f                                                   | 5,5         | 5,5         | 5,5         | 5,5         | 5,5         | 5,5         |
|                     | g                                                   | 8           | 8           | 8           | 8           | 8           | 8           |
|                     | g-1                                                 | 2           | 2           | 2           | 2           | 2           | 2           |
|                     | h                                                   | 83          | 88          | 95          | 99          | 99          | 105         |
|                     | i                                                   | 78          | 85          | 96          | 103         | 103         | 110         |
|                     | k                                                   | 21          | 21          | 21          | 28          | 28          | 38          |
|                     | l                                                   | 43          | 52          | 54          | 60          | 60          | 65          |
|                     | Terminal for cond. cross<br>section (mm²) min.-max. | 1.5 1.5 1.5 | 2.5 2.5 2.5 | 2.5 2.5 2.5 | 2.5 2.5 2.5 | 2.5 2.5 2.5 | 2.5 2.5 2.5 |