

**Network enclosure AMAXX®**  
Part no. 25102




- network enclosure made of AMAPLAST
- protection type IP 44
- top part electric grey RAL 7035 or yellow RAL 1021, bottom part black with screw-in nuts for installation of a floor-mounted base
- including a height-adjustable mounting rail
- cable gland set with multiple seal

Technical specifications

|                           |   |
|---------------------------|---|
| Data port sockets         | 2 Cepex data port sockets identical lock, prepared for 4 RJ45 connection module couplings, type E-DAT module, port, cat.6, brand: BTR (part no. 41455) or OpDAT module LC or ST (brand BTR - not delivery contains)   |
| Connection / feeder cable | <ul style="list-style-type: none"><li>• each x M 25 top and bottom (sealed)</li><li>• each x M 20 top and bottom (sealed)</li><li>• cable gland M 25 bottom (multiple seal with 3 openings for a cable diameter of 5-7 mm including suitable blanking plugs, 1 cap-shape seal blank for punched hole)</li></ul> |
| Protection type           | IP 44   |
| Shutter                   | false   |
| Enclosure material        | Plastic   |
| Weight                    | 1550 g  |
| Height                    | 130 mm  |
| Width                     | 225 mm  |

Drawing



Drawing 1 MB 531

Depth dimensions at various fittings.

| Receptacles        | Degrees | Depth  |
|--------------------|---------|--------|
| SCHUKO® 16A, 230 V | IP 44   | 175 mm |
|                    | IP 67   | 194 mm |
| CEE 16A, 3p, 230V  | IP 44   | 204 mm |
|                    | IP 67   | 205 mm |
| CEE 16A, 5p, 400V  | IP 44   | 209 mm |
|                    | IP 67   | 213 mm |
| CEE 32A, 5p, 400V  | IP 44   | 221 mm |
|                    | IP 67   | 227 mm |
| CEE 63A, 5p, 400V  | IP 44   | 248 mm |
|                    | IP 67   | 248 mm |

Cable entries: closed for cut out. 2 x M 25 each on top and bottom, 2 x M 20 each on top and bottom for cut out.