

**Plug AM-TOP®**  
Part no. 260ZD




- screw terminals
- single part body
- highly heat resistant contact carrier
- nickel plated contacts
- cable gland and sealing
- strain relief and protection against kinking

Technical specifications

|                       |                                                               |
|-----------------------|---------------------------------------------------------------|
| Ampere                | 32 A                                                          |
| Poles                 | 3 p                                                           |
| Voltage               | 230 V                                                         |
| Clock position        | 6 h                                                           |
| Hertz                 | 50-60 Hz                                                      |
| Connection technology | Screw terminals                                               |
| Contact               | nickel plated contacts, highly heat resistant contact carrier |
| Protection type       | IP 44                                                         |
| Weight                | 249 g                                                         |

Drawing



| Drawing<br>2 MB 217      | Amp.<br>Poles | 16    |       |       | 32  |     |      |
|--------------------------|---------------|-------|-------|-------|-----|-----|------|
|                          |               | 3     | 4     | 5     | 3   | 4   | 5    |
| Dim. in mm               | a             | 142   | 147   | 147   | 186 | 186 | 180  |
|                          | b             | 53    | 59    | 67    | 70  | 70  | 77   |
|                          | h             | 59    | 69.4  | 76    | 81  | 81  | 89.5 |
|                          | n             | 105.2 | 110.5 | 110.5 | 141 | 141 | 135  |
|                          | y             | 14.5  | 16    | 16    | 22  | 22  | 22   |
| Terminal for cond. cross |               | 1     | 1     | 1     | 2.5 | 2.5 | 2.5  |
| section (mm²) min.-max.  |               | —2.5  | —2.5  | —2.5  | —6  | —6  | —6   |