

Panel mounted receptacles with TwinCONTACT

Part no. 3124




- screwless spring terminals
- standard flange dimensions
- 20° inclination
- receptacles are designed for adding an auxiliary contact switch

Technical specifications

Ampere	32 A
Poles	3 p
Voltage	110 V
Clock position	4 h
Hertz	50-60 Hz
Connection technology	Screwless - TwinCONTACT
Contact	standard
Protection type	IP 44
Flange	85x85 mm
Fixing hole	70x70 mm
Inclination	20 °
Weight	207 g
Declaration of Conformity	DE,VDE

Drawing



Drawing		16			32		
1 MB 519		3			3		
Dim. in mm		Poles			Poles		
a		85	85	85	85	85	85
b		85	85	85	85	85	85
c		52	57	55	61	60	66
d		70	70	70	70	70	70
e		70	70	70	70	70	70
f		5.5	5.5	5.5	5.5	5.5	5.5
g		8	8	8	8	8	8
g.1		2	2	2	2	2	2
h		86	96	100	96	104	110
k		31	32	33	43	44	48
I min.		57	64	70	78	78	78
I max.		76	76	76	78	78	78
ø		20	20	20	20	20	20
Terminal for cond. cross		1.5	1.5	1.5	2.5	2.5	2.5
section (mm²) min.-max.		—4	—4	—4	—10	—10	—10