

Wall mounted phase inverter inlet  
Part no. 3517




- screw terminals
- external fixing
- hinged lid for retrofit see accessories

Technical specifications

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 16 A            |
| Poles                     | 5 p             |
| Voltage                   | 400 V           |
| Clock position            | 6 h             |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Weight                    | 215 g           |
| Declaration of Conformity | DE,VDE          |

Drawing



| Drawing<br>2 MB 221<br>Dim. in mm | Amp.<br>Poles | 16     |        | 32     |        |        |
|-----------------------------------|---------------|--------|--------|--------|--------|--------|
|                                   |               | 4      | 5      | 3      | 4      | 5      |
| a                                 |               | 92.5   | 92.5   | 102    | 102    | 102    |
| b                                 |               | 87     | 87     | 94     | 94     | 94     |
| c                                 |               | 84.5   | 84.5   | 94     | 94     | 94     |
| d                                 |               | 55.5   | 55.5   | 62     | 62     | 62     |
| e                                 |               | 76     | 76     | 84     | 84     | 84     |
| f1                                |               | 5.3    | 5.3    | 5.3    | 5.3    | 5.3    |
| f2                                |               | 5.3    | 5.3    | 5.3    | 5.3    | 5.3    |
| h                                 |               | 128    | 128    | 146    | 146    | 146    |
| i                                 |               | 21.5   | 21.5   | 26     | 26     | 26     |
| M                                 |               | 25x1.5 | 25x1.5 | 25x1.5 | 25x1.5 | 32x1.5 |