

**Connector PowerTOP®**  
Part no. 3881




- screw terminals
- with highly heat resistant contact carrier
- cable gland and external cable grip

Technical specifications

|                           |                                       |
|---------------------------|---------------------------------------|
| Ampere                    | 16 A                                  |
| Poles                     | 5 p                                   |
| Voltage                   | 400 V                                 |
| Clock position            | 6 h                                   |
| Hertz                     | 50-60 Hz                              |
| Connection technology     | Screw terminals                       |
| Contact                   | highly heat resistant contact carrier |
| Protection type           | IP 67                                 |
| Weight                    | 310 g                                 |
| Declaration of Conformity | DE,VDE, CN,CQC                        |

Drawing



| Drawing<br>3 MB 48/3     | Amp.<br>Poles | 16   |      |      | 32   |      |      |
|--------------------------|---------------|------|------|------|------|------|------|
|                          |               | 3    | 4    | 5    | 3    | 4    | 5    |
| Dim. in mm               | a             | 171  | 182  | 194  | 217  | 217  | 229  |
|                          | b             | 78   | 85   | 96   | 103  | 103  | 110  |
|                          | h             | 79   | 88   | 95   | 99   | 99   | 105  |
|                          | y             | 19   | 19   | 22   | 24.5 | 24.5 | 28.5 |
| Terminal for cond. cross |               | 1    | 1    | 1    | 2.5  | 2.5  | 2.5  |
| section (mm²) min.-max.  |               | —2.5 | —2.5 | —2.5 | —6   | —6   | —6   |