


Panel mounted inlet  
Part no. 410




- screw terminals
- with hinged lid

Technical specifications

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 32 A            |
| Poles                     | 5 p             |
| Voltage                   | 110 V           |
| Clock position            | 4 h             |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Weight                    | 365 g           |
| Declaration of Conformity | DE,VDE          |

Drawing



| Drawing<br>2 MB 43                                  | Amp.<br>Poles | 16   |      | 32  |     |     |
|-----------------------------------------------------|---------------|------|------|-----|-----|-----|
|                                                     |               | 4    | 5    | 3   | 4   | 5   |
| Dim. in mm                                          | a             | 85   | 85   | 75  | 75  | 75  |
|                                                     | b             | 85   | 85   | 90  | 90  | 90  |
|                                                     | c             | 104  | 106  | 115 | 115 | 117 |
|                                                     | d             | 64   | 64   | 45  | 45  | 45  |
|                                                     | d1            | 10   | 10   | 13  | 13  | 13  |
|                                                     | e             | 64   | 64   | 78  | 78  | 78  |
|                                                     | f             | 5.5  | 5.5  | 5.5 | 5.5 | 5.5 |
|                                                     | g             | 27   | 27   | 27  | 27  | 27  |
|                                                     | g.1           | 2    | 2    | 1   | 1   | 1   |
|                                                     | h             | 140  | 140  | 150 | 150 | 150 |
|                                                     | l             | 50   | 50   | 55  | 55  | 55  |
| Terminal for cond. cross<br>section (mm²) min.-max. | 1             | 1    | 2.5  | 2.5 | 2.5 | 2.5 |
|                                                     |               | -2.5 | -2.5 | -6  | -6  | -6  |