

Wall mounted receptacle  
Part no. 5628A




- screw terminals
- switched
- mechanical DUO-interlock
- 3 pole fuse socket D 02
- receptacles can be padlocked

Technical specifications

|                       |                 |
|-----------------------|-----------------|
| Ampere                | 32 A            |
| Poles                 | 5 p             |
| Voltage               | 400 V           |
| Clock position        | 6 h             |
| Hertz                 | 50-60 Hz        |
| Connection technology | Screw terminals |
| Contact               | standard        |
| Protection type       | IP 44           |
| Enclosure material    | Plastic         |
| Weight                | 2340 g          |

Drawing



|                     |                                                  |       |       |       |       |       |      |      |
|---------------------|--------------------------------------------------|-------|-------|-------|-------|-------|------|------|
| Drawing<br>1 MB 208 | Amp.<br>Poles                                    | 16    |       |       | 32    |       | 63   |      |
|                     |                                                  | 3     | 4     | 5     | 4     | 5     | 4    | 5    |
| Dim. in mm          | a                                                | 364   | 364   | 364   | 364   | 364   | 460  | 460  |
|                     | b                                                | 134   | 134   | 134   | 134   | 134   | 180  | 180  |
|                     | c                                                | 160   | 162   | 163   | 168   | 168   | 195  | 195  |
|                     | d                                                | 347   | 347   | 347   | 347   | 347   | 440  | 440  |
|                     | e                                                | 117   | 117   | 117   | 117   | 117   | 160  | 160  |
|                     | f                                                | 6.3   | 6.3   | 6.3   | 6.3   | 6.3   | 8.1  | 8.1  |
|                     | g                                                | 8     | 8     | 8     | 8     | 8     | 8    | 8    |
|                     | h                                                | 391   | 395   | 398   | 408   | 411   | 502  | 502  |
|                     | M                                                | 32/40 | 32/40 | 32/40 | 32/40 | 32/40 | 40   | 40   |
|                     | M*                                               | 2x32  | 2x32  | 2x32  | 2x32  | 2x32  | 2x40 | 2x40 |
|                     | Max. cable diam. (mm)                            | 27    | 27    | 27    | 27    | 27    | 27   | 27   |
|                     | Terminal for cond. cross section (mm²) min.-max. | 1.5   | 1.5   | 1.5   | 2.5   | 2.5   | 6    | 6    |