


**Panel mounted receptacle**  
Part no. 611




- screw terminals straight

**Technical specifications**

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 16 A            |
| Poles                     | 3 p             |
| Voltage                   | 40-50 V         |
| Clock position            | 12 h            |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Flange                    | 55x55 mm        |
| Fixing hole               | 45x45 mm        |
| Weight                    | 130 g           |
| Declaration of Conformity | CN,CQC          |

**Drawing**



| Drawing<br>1 MB 136 | Amp.<br>Poles                                                    | 16  |     | 32  |     |
|---------------------|------------------------------------------------------------------|-----|-----|-----|-----|
|                     |                                                                  | 2   | 3   | 2   | 3   |
| Dim. in mm          | a                                                                | 55  | 55  | 55  | 55  |
|                     | b                                                                | 55  | 55  | 55  | 55  |
|                     | c                                                                | 44  | 44  | 44  | 44  |
|                     | d                                                                | 45  | 45  | 45  | 45  |
|                     | e                                                                | 45  | 45  | 45  | 45  |
|                     | f                                                                | 4.2 | 4.2 | 4.2 | 4.2 |
|                     | g.                                                               | 8   | 8   | 8   | 8   |
|                     | g.1                                                              | 2   | 2   | 2   | 2   |
|                     | h                                                                | 67  | 67  | 67  | 67  |
|                     | k                                                                | 22  | 22  | 22  | 22  |
|                     | l                                                                | 34  | 34  | 34  | 34  |
|                     | Terminal for cond. cross<br>section (mm <sup>2</sup> ) min.-max. | 4   | 4   | 4   | 4   |
|                     |                                                                  | —10 | —10 | —10 | —10 |