


Panel mounted receptacle  
Part no. 622




- screw terminals
- straight

Technical specifications

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 32 A            |
| Poles                     | 2 p             |
| Voltage                   | 50 V            |
| Clock position            | 10 h            |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Flange                    | 55x55 mm        |
| Fixing hole               | 45x45 mm        |
| Weight                    | 108 g           |
| Declaration of Conformity | CN,CQC          |

Drawing



| Drawing<br>1 MB 136                                 | Amp.<br>Poles | 16  |         | 32  |         |
|-----------------------------------------------------|---------------|-----|---------|-----|---------|
|                                                     |               | 2   | 3       | 2   | 3       |
| Dim. in mm                                          | a             | 55  | 55      | 55  | 55      |
|                                                     | b             | 55  | 55      | 55  | 55      |
|                                                     | c             | 44  | 44      | 44  | 44      |
|                                                     | d             | 45  | 45      | 45  | 45      |
|                                                     | e             | 45  | 45      | 45  | 45      |
|                                                     | f             | 4.2 | 4.2     | 4.2 | 4.2     |
|                                                     | g             | 8   | 8       | 8   | 8       |
|                                                     | g.1           | 2   | 2       | 2   | 2       |
|                                                     | h             | 67  | 67      | 67  | 67      |
|                                                     | k             | 22  | 22      | 22  | 22      |
|                                                     | l             | 34  | 34      | 34  | 34      |
| Terminal for cond. cross<br>section (mm²) min.-max. |               | 4 4 | —10 —10 | 4 4 | —10 —10 |