

Wall mounted receptacle  
Part no. 7027




- screw terminals
- X-CONTACT®
- contactor and electrical PCS interlock

Technical specifications

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 125 A           |
| Poles                     | 4 p             |
| Voltage                   | 230 V           |
| Clock position            | 9 h             |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | X-CONTACT®      |
| Protection type           | IP 67           |
| Enclosure material        | Plastic         |
| Weight                    | 8500 g          |
| Declaration of Conformity | CN,CQC          |

Drawing



| Drawing                              | Amp.  | 125       |
|--------------------------------------|-------|-----------|
| 1 MB 163                             | Poles | 4 5       |
| Dim. in mm                           | a     | 460 460   |
|                                      | b     | 260 260   |
|                                      | c     | 234 234   |
|                                      | d     | 434 434   |
|                                      | e     | 234 234   |
|                                      | f     | 11 11     |
|                                      | g     | 9 9       |
|                                      | h     | 519 519   |
|                                      | M     | 63 63     |
|                                      | M*    | 2x63 2x63 |
| Max. cable diam. (mm)                |       | 44 44     |
| Terminal for cond. cross             |       | 25 25     |
| section (mm <sup>2</sup> ) min.-max. |       | —70 —70   |