

AMAXX® s receptacle combination

Part no. 960012




- pre-wired for installation
- enclosure and insert made of AMAPLAST
- fusing behind a transparent cover

Technical specifications

CEE 32 A, 5 p, 400 V	1
SCHUKO® 16 A, 230 V	2
Fusing	<ul style="list-style-type: none"> • 1 RCD 40 A, 4 p, 0.03 A • 1 MCB 32 A, 3 p, C • 1 MCB 16 A, 1 p, C
Pre-fuse max.	40 A
InA	40 A
RDF	1
Connection / feeder cable	<ul style="list-style-type: none"> • for 1 cable up to 5 x 10 mm²
Protection type	IP 44
Shutter	false
Enclosure material	Plastic
Weight	3960 g
Height	650 mm
Width	112.5 mm

Drawing



Drawing 1 MB 541

Depth dimensions at various fittings.

Receptacles	Degrees	Depth
SCHUKO® 16A, 230 V	IP 44	140 mm
	IP 67	157 mm
CEE 16A, 3p, 230V	IP 44	170 mm
	IP 67	169 mm
CEE 16A, 5p, 400V	IP 44	172 mm
	IP 67	174 mm
CEE 32A, 5p, 400V	IP 44	182 mm
	IP 67	188 mm

Cable entries: closed for cut out. 1 x M 25 on top and 1 x M 25 on bottom or 1 x M 32 on top and 1 x M 32 on bottom, additionally: 1 x M 20 on top and bottom to cut out.