

**Panel mounted receptacle**  
Part no. 1471




- screw terminals
- 20° inclination

**Technical specifications**

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 16 A            |
| Poles                     | 5 p             |
| Voltage                   | 110 V           |
| Clock position            | 4 h             |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Flange                    | 100x92 mm       |
| Fixing hole               | 85x77 mm        |
| Inclination               | 20 °            |
| Weight                    | 204 g           |
| Declaration of Conformity | CN,CQC          |

**Drawing**



| Drawing<br>1 MB 260<br>Dim. in mm                   | Amp.<br>Poles | 16        |           |           | 32         |            |            |
|-----------------------------------------------------|---------------|-----------|-----------|-----------|------------|------------|------------|
|                                                     |               | 3         | 4         | 5         | 3          | 4          | 5          |
| a                                                   |               | 73.5      | 100       | 100       | 100        | 100        | 100        |
| b                                                   |               | 64        | 92        | 92        | 92         | 92         | 92         |
| c                                                   |               | 50        | 59        | 58        | 62         | 62         | 61         |
| d                                                   |               | 60        | 85        | 85        | 85         | 85         | 85         |
| e                                                   |               | 52        | 77        | 77        | 77         | 77         | 77         |
| f                                                   |               | 5.5       | 5.5       | 5.5       | 5.5        | 5.5        | 5.5        |
| g                                                   |               | 7         | 8         | 8         | 8          | 8          | 8          |
| g-1                                                 |               | 2         | 2         | 2         | 2          | 2          | 2          |
| h                                                   |               | 79        | 100       | 100       | 103        | 103        | 106        |
| k                                                   |               | 44        | 34        | 34        | 54         | 54         | 49         |
| l                                                   |               | 52        | 55        | 65        | 67         | 67         | 72         |
| l1                                                  |               | 60        | 63        | 72        | 82         | 82         | 85         |
| α                                                   |               | 20°       | 20°       | 20°       | 20°        | 20°        | 20°        |
| Terminal for cond. cross<br>section (mm²) min.-max. |               | 1.5<br>—4 | 1.5<br>—4 | 1.5<br>—4 | 2.5<br>—10 | 2.5<br>—10 | 2.5<br>—10 |