


**Plug PowerTOP® Xtra**  
Part no. 13206




- screw terminals
- rubberised grip area
- frame terminals
- highly heat resistant contact carrier
- nickel plated contacts
- cable gland and sealing
- strain relief and protection against kinking
- enclosure with thread lock
- two safety slides

Technical specifications

|                           |                                                               |
|---------------------------|---------------------------------------------------------------|
| Ampere                    | 63 A                                                          |
| Poles                     | 4 p                                                           |
| Voltage                   | 400 V                                                         |
| Clock position            | 6 h                                                           |
| Hertz                     | 50-60 Hz                                                      |
| Connection technology     | Screw terminals                                               |
| Contact                   | highly heat resistant contact carrier, nickel plated contacts |
| Protection type           | IP 67                                                         |
| Weight                    | 826 g                                                         |
| Declaration of Conformity | VDE, EAC, CQC                                                 |

Drawing



| Drawing<br>2 MB 225                  | Amp.<br>Poles | 63  |     |     | 125 |     |     |
|--------------------------------------|---------------|-----|-----|-----|-----|-----|-----|
|                                      |               | 3   | 4   | 5   | 3   | 4   | 5   |
| Dim. in mm                           | a             | 250 | 250 | 250 | 290 | 290 | 290 |
|                                      | b             | 114 | 114 | 114 | 130 | 130 | 130 |
|                                      | y             | 36  | 36  | 36  | 49  | 49  | 49  |
| Terminal for cond. cross             |               | 6   | 6   | 6   | 25  | 25  | 25  |
| section (mm <sup>2</sup> ) min.-max. |               | —16 | —16 | —16 | —50 | —50 | —50 |