

Wall mounted receptacle with TwinCONTACT  
Part no. 1753



- screwless spring terminals
- suitable for through wiring
- internal fixing
- enclosure base can be turned 180°
- receptacles are designed for adding an auxiliary contact switch

Technical specifications

|                           |                         |
|---------------------------|-------------------------|
| Ampere                    | 16 A                    |
| Poles                     | 4 p                     |
| Voltage                   | 50-500 V                |
| Clock position            | 10 h                    |
| Hertz                     | 100-300 Hz              |
| Connection technology     | Screwless - TwinCONTACT |
| Contact                   | standard                |
| Protection type           | IP 44                   |
| Weight                    | 230 g                   |
| Declaration of Conformity | VDE, EAC, CQC           |

Drawing



| Drawing<br>1 MB 43                                  | Amp.<br>Poles | 16                         |     | 32                         |       |       |
|-----------------------------------------------------|---------------|----------------------------|-----|----------------------------|-------|-------|
|                                                     |               | 4                          | 5   | 3                          | 4     | 5     |
| Dim. in mm                                          | a             | 128                        | 128 | 128                        | 128   | 128   |
|                                                     | b             | 84                         | 84  | 84                         | 84    | 84    |
|                                                     | c             | 122                        | 124 | 136                        | 136   | 138   |
|                                                     | d             | 11                         | 11  | 11                         | 11    | 11    |
|                                                     | e             | 68                         | 68  | 68                         | 68    | 68    |
|                                                     | f             | 5.3                        | 5.3 | 5.3                        | 5.3   | 5.3   |
|                                                     | g             | 4                          | 4   | 4                          | 4     | 4     |
|                                                     | h             | 144                        | 145 | 158                        | 158   | 160   |
|                                                     | M             | 25                         | 25  | 32                         | 32    | 32    |
|                                                     | M*            | 2x25 (blind) to be cut out |     | 2x25 (blind) to be cut out |       |       |
| Max. cable diam. (mm)                               |               | 18                         | 18  | 18/25                      | 18/25 | 18/25 |
| Terminal for cond. cross<br>section (mm²) min.-max. |               | 1.5                        | 1.5 | 2.5                        | 2.5   | 2.5   |
|                                                     |               | —4                         | —4  | —10                        | —10   | —10   |