


Panel mounted inlet TM
Part no. 20462




- screw terminals
- highly heat resistant contact carrier
- nickel plated contacts
- with protective cap
- (form BP)

Technical specifications

Ampere	32 A
Poles	5 p
Voltage	400 V
Clock position	6 h
Hertz	50-60 Hz
Connection technology	Screw terminals
Contact	standard
Protection type	IP 67
Weight	400 g
Declaration of Conformity	VDE, EAC

Drawing



Drawing	Amp.	16			32			63		
2 MB 62	Poles	3	5	3	4	5	3	4	5	
Dim. in mm	a	85	85	85	85	85	108	108	108	
	b	85	85	85	85	85	101	101	101	
	c	132	132	131	131	137	164	164	164	
	d	70	70	70	70	70	85	85	85	
	e	70	70	70	70	70	77	77	77	
	f	6.3	6.3	6.3	6.3	6.3	6.5	6.5	6.5	
	g	11	11	11	11	11	12	12	12	
	g.1	2	2	2	2	2	2	2	2	
	h	100	107	108	108	111	130	130	130	
	s	70	87	94	94	102	114	114	114	
	l	30	30	30	30	30	40	40	40	
Terminal for cond. cross	1	1	2,5	2,5	2,5	2,5	6	6	6	
section (mm²) min.-max.		-2,5 -2,5	-6 -6	-6 -6	-6 -6	-6 -6	-16 -16	-16 -16	-16 -16	