

**Connector AM-TOP®**  
Part no. 21021ZB



- screw terminals
- single part body
- with highly heat resistant contact carrier
- nickel plated contacts
- cable gland and sealing
- strain relief and protection against kinking

Technical specifications

|                           |                                                               |
|---------------------------|---------------------------------------------------------------|
| Ampere                    | 16 A                                                          |
| Poles                     | 4 p                                                           |
| Voltage                   | 400 V                                                         |
| Clock position            | 6 h                                                           |
| Hertz                     | 50-60 Hz                                                      |
| Connection technology     | Screw terminals                                               |
| Contact                   | highly heat resistant contact carrier, nickel plated contacts |
| Protection type           | IP 44                                                         |
| Weight                    | 202 g                                                         |
| Declaration of Conformity | EAC                                                           |

Drawing



| Drawing<br>3 MB 63       | Amp.<br>Poles | 16   |      |      | 32  |     |     |
|--------------------------|---------------|------|------|------|-----|-----|-----|
|                          |               | 3    | 4    | 5    | 3   | 4   | 5   |
| Dim. in mm               | a             | 162  | 165  | 167  | 209 | 209 | 208 |
|                          | b             | 60   | 68   | 76   | 82  | 82  | 89  |
|                          | h             | 83   | 92   | 98   | 100 | 100 | 108 |
|                          | y             | 14.5 | 16   | 16   | 22  | 22  | 22  |
| Terminal for cond. cross |               | 1    | 1    | 1    | 2.5 | 2.5 | 2.5 |
| section (mm²) min.-max.  |               | —2.5 | —2.5 | —2.5 | —6  | —6  | —6  |