

**Panel mounted receptacle**  
Part no. 2289A




- screw terminals
- straight

**Technical specifications**

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 16 A            |
| Poles                     | 3 p             |
| Voltage                   | 50-250 V        |
| Clock position            | 3 h             |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 67           |
| Flange                    | 75x75 mm        |
| Fixing hole               | 60x60 mm        |
| Weight                    | 160 g           |
| Declaration of Conformity | VDE, EAC, CQC   |

**Drawing**



| Drawing<br>1 MB 141 | Amp.<br>Poles                                                    | 16  |     |     | 32  |     |     |
|---------------------|------------------------------------------------------------------|-----|-----|-----|-----|-----|-----|
|                     |                                                                  | 3   | 4   | 5   | 3   | 4   | 5   |
| Dim. in mm          | a                                                                | 75  | 75  | 75  | 85  | 85  | 85  |
|                     | b                                                                | 75  | 75  | 75  | 75  | 75  | 75  |
|                     | c                                                                | 60  | 61  | 61  | 70  | 70  | 72  |
|                     | d                                                                | 60  | 60  | 60  | 60  | 60  | 60  |
|                     | e                                                                | 60  | 60  | 60  | 60  | 60  | 60  |
|                     | f                                                                | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 |
|                     | g                                                                | 8   | 8   | 8   | 8   | 8   | 8   |
|                     | g.1                                                              | 2   | 2   | 2   | 2   | 2   | 2   |
|                     | h                                                                | 83  | 88  | 95  | 99  | 99  | 105 |
|                     | i                                                                | 78  | 85  | 96  | 103 | 103 | 110 |
|                     | k                                                                | 31  | 32  | 32  | 39  | 39  | 39  |
|                     | l                                                                | 43  | 52  | 54  | 58  | 58  | 65  |
|                     | Terminal for cond. cross<br>section (mm <sup>2</sup> ) min.-max. | 1.5 | 1.5 | 1.5 | 2.5 | 2.5 | 2.5 |
|                     |                                                                  | —4  | —4  | —4  | —10 | —10 | —10 |