

Wall mounted receptacle  
Part no. 22932




- screw terminals
- highly heat resistant contact carrier
- nickel plated contacts
- internal fixing
- enclosure base can be turned 180°

Technical specifications

|                           |                                                               |
|---------------------------|---------------------------------------------------------------|
| Ampere                    | 16 A                                                          |
| Poles                     | 4 p                                                           |
| Voltage                   | 500 V                                                         |
| Clock position            | 7 h                                                           |
| Hertz                     | 50-60 Hz                                                      |
| Connection technology     | Screw terminals                                               |
| Contact                   | highly heat resistant contact carrier, nickel plated contacts |
| Protection type           | IP 44                                                         |
| Weight                    | 303 g                                                         |
| Declaration of Conformity | EAC                                                           |

Drawing



| 1 MB 209<br>1 MB 43                              | Amp.<br>Poles | 16                               |     |     | 32                          |       |       |
|--------------------------------------------------|---------------|----------------------------------|-----|-----|-----------------------------|-------|-------|
|                                                  |               | 3                                | 4   | 5   | 3                           | 4     | 5     |
| Dim. in mm                                       | a             | 87                               | 128 | 128 | 128                         | 128   | 128   |
|                                                  | b             | 64                               | 84  | 84  | 84                          | 84    | 84    |
|                                                  | c             | 99                               | 122 | 124 | 136                         | 136   | 138   |
|                                                  | d             | 40                               | 11  | 11  | 11                          | 11    | 11    |
|                                                  | e             | 50                               | 68  | 68  | 68                          | 68    | 68    |
|                                                  | f             | 4.5                              | 5.3 | 5.3 | 5.3                         | 5.3   | 5.3   |
|                                                  | g.            | 4                                | 4   | 4   | 4                           | 4     | 4     |
|                                                  | h             | 115                              | 144 | 145 | 158                         | 158   | 160   |
|                                                  | M             | 20                               | 25  | 25  | 32                          | 32    | 32    |
|                                                  | M*            | M 20 2xM25 (blind) to be cut out |     |     | 2xM25 (blind) to be cut out |       |       |
| Max. cable diam. (mm)                            |               | 15                               | 18  | 18  | 18/25                       | 18/25 | 18/25 |
| Terminal for cond. cross section (mm²) min.-max. |               | 1.5                              | 1.5 | 1.5 | 2.5                         | 2.5   | 2.5   |
|                                                  |               | —4                               | —4  | —4  | —10                         | —10   | —10   |