

Panel mounted receptacle TM
Part no. 24630




- screw terminals
- highly heat resistant contact carrier
- nickel plated contacts
- 20° inclination
- (form BS)

Technical specifications

Ampere	16 A
Poles	3 p
Voltage	230 V
Clock position	6 h
Hertz	50-60 Hz
Connection technology	Screw terminals
Contact	highly heat resistant contact carrier, nickel plated contacts
Protection type	IP 67
Flange	85x85 mm
Fixing hole	70x70 mm
Inclination	20 °
Weight	176 g
Declaration of Conformity	VDE, EAC

Drawing



Drawing 1 MB 474	Amp.	16		32		63
	Pole	3	5	3/4	5	3/4/5
Dim. in mm	a	85	85	85	85	114
	b	85	85	85	85	114
	c	71	65	65	80	98
	d	70	70	70	70	90
	e	70	70	70	70	90
	f	5.5	5.5	5.5	5.5	5.5
	g	8	8	8	8	12
	g.1	2	2	2	2	2
	h	92	98	101	115	135
	i	70	87	94	101	112
	k	39	33	53	53	70
	I min.	57	70	78	78	92
	I max.	78	78	78	78	105
Terminal for cond. cross section (mm²) min.-max.	It	—	—	—	—	105
		1.5	1.5	2.5	2.5	6
		—4	—4	—10	—10	—25