

Panel mounted receptacle TM  
Part no. 24640




- screw terminals
- highly heat resistant contact carrier
- nickel plated contacts
- 20° inclination
- (form BS)

Technical specifications

|                           |                                                               |
|---------------------------|---------------------------------------------------------------|
| Ampere                    | 16 A                                                          |
| Poles                     | 5 p                                                           |
| Voltage                   | 400 V                                                         |
| Clock position            | 6 h                                                           |
| Hertz                     | 50-60 Hz                                                      |
| Connection technology     | Screw terminals                                               |
| Contact                   | highly heat resistant contact carrier, nickel plated contacts |
| Protection type           | IP 67                                                         |
| Flange                    | 85x85 mm                                                      |
| Fixing hole               | 70x70 mm                                                      |
| Inclination               | 20 °                                                          |
| Weight                    | 233 g                                                         |
| Declaration of Conformity | VDE, EAC                                                      |

Drawing



|                          |      |     |     |     |     |       |
|--------------------------|------|-----|-----|-----|-----|-------|
| Drawing<br>1 MB 474      | Amp. | 16  |     | 32  |     | 63    |
|                          | Pole | 3   | 5   | 3/4 | 5   | 3/4/5 |
| Dim. in mm               |      |     |     |     |     |       |
| a                        | 85   | 85  | 85  | 85  | 114 |       |
| b                        | 85   | 85  | 85  | 85  | 114 |       |
| c                        | 71   | 65  | 65  | 80  | 98  |       |
| d                        | 70   | 70  | 70  | 70  | 90  |       |
| e                        | 70   | 70  | 70  | 70  | 90  |       |
| f                        | 5.5  | 5.5 | 5.5 | 5.5 | 5.5 |       |
| g                        | 8    | 8   | 8   | 8   | 12  |       |
| g.1                      | 2    | 2   | 2   | 2   | 2   |       |
| h                        | 92   | 98  | 101 | 115 | 135 |       |
| i                        | 70   | 87  | 94  | 101 | 112 |       |
| k                        | 39   | 33  | 53  | 53  | 70  |       |
| I min.                   | 57   | 70  | 78  | 78  | 92  |       |
| I max.                   | 78   | 78  | 78  | 78  | 105 |       |
| It                       | —    | —   | —   | —   | 105 |       |
| Terminal for cond. cross |      |     |     |     |     |       |
| section (mm²) min.-max.  |      |     |     |     |     |       |
|                          | 1.5  | 1.5 | 2.5 | 2.5 | 6   |       |
|                          | —4   | —4  | —10 | —10 | —25 |       |