

Panel mounted receptacle  
Part no. 3054



- screw terminals
- straight

Technical specifications

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 16 A            |
| Poles                     | 3 p             |
| Voltage                   | 50-500 V        |
| Clock position            | 10 h            |
| Hertz                     | 100-300 Hz      |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Flange                    | 75x75 mm        |
| Fixing hole               | 60x60 mm        |
| Weight                    | 137 g           |
| Declaration of Conformity | EAC, CQC        |

Drawing



| Drawing<br>1 MB 247 | Amp.<br>Poles                                                    | 16  |     |     | 32  |     |     |
|---------------------|------------------------------------------------------------------|-----|-----|-----|-----|-----|-----|
|                     |                                                                  | 3   | 4   | 5   | 3   | 4   | 5   |
| Dim. in mm          | a                                                                | 75  | 75  | 75  | 75  | 75  | 75  |
|                     | b                                                                | 75  | 75  | 75  | 75  | 75  | 75  |
|                     | c                                                                | 53  | 53  | 55  | 64  | 64  | 65  |
|                     | d                                                                | 60  | 60  | 60  | 60  | 60  | 60  |
|                     | e                                                                | 60  | 60  | 60  | 60  | 60  | 60  |
|                     | f                                                                | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 |
|                     | g                                                                | 8   | 8   | 8   | 8   | 8   | 8   |
|                     | g1                                                               | 2   | 2   | 2   | 2   | 2   | 2   |
|                     | h                                                                | 75  | 80  | 83  | 89  | 89  | 100 |
|                     | h1                                                               |     | 6   | 8   | 11  | 11  | 12  |
|                     | k                                                                | 31  | 32  | 32  | 39  | 39  | 39  |
|                     | l                                                                | 43  | 52  | 54  | 58  | 58  | 62  |
|                     | Terminal for cond. cross<br>section (mm <sup>2</sup> ) min.-max. | 1.5 | 1.5 | 1.5 | 2.5 | 2.5 | 2.5 |
|                     |                                                                  | -4  | -4  | -4  | -10 | -10 | -10 |