


Phase inverter plug AM-TOP®  
Part no. 339




- screw terminals
- single part body
- cable gland and sealing
- strain relief and protection against kinking

Technical specifications

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 16 A            |
| Poles                     | 4 p             |
| Voltage                   | 400 V           |
| Clock position            | 6 h             |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Weight                    | 155 g           |
| Declaration of Conformity | VDE, EAC, CQC   |

Drawing



| Drawing<br>2 MB 217      | Amp.<br>Poles | 16    |       |       | 32  |     |      |
|--------------------------|---------------|-------|-------|-------|-----|-----|------|
|                          |               | 3     | 4     | 5     | 3   | 4   | 5    |
| Dim. in mm               | a             | 142   | 147   | 147   | 186 | 186 | 180  |
|                          | b             | 53    | 59    | 67    | 70  | 70  | 77   |
|                          | h             | 59    | 69.4  | 76    | 81  | 81  | 89.5 |
|                          | n             | 105.2 | 110.5 | 110.5 | 141 | 141 | 135  |
|                          | y             | 14.5  | 16    | 16    | 22  | 22  | 22   |
| Terminal for cond. cross |               | 1     | 1     | 1     | 2.5 | 2.5 | 2.5  |
| section (mm²) min.-max.  |               | —2.5  | —2.5  | —2.5  | —6  | —6  | —6   |