

## **Connector AM-TOP®**

Part no. 522ZB




- screw terminals
- single part body
- with highly heat resistant contact carrier nickel plated contacts
- cable gland and sealing
- strain relief and protection against kinking

## Technical specifications

| Ampere                    | 32 A                                  |
|---------------------------|---------------------------------------|
| Poles                     | 3 p                                   |
| Voltage                   | 230 V                                 |
| Clock position            | 6 h                                   |
| Hertz                     | 50-60 Hz                              |
| Connection technology     | Screw terminals                       |
| Contact                   | highly heat resistant contact carrier |
| Protection type           | IP 44                                 |
| Weight                    | 313 g                                 |
| Declaration of Conformity | EAC                                   |

## Drawing



| Drawing                  | Amp.  | l    | 10           |      |     | 32  |     |
|--------------------------|-------|------|--------------|------|-----|-----|-----|
| 3 MB 63                  | Poles | 3    | 4            | 5    | 3   | 4   | 5   |
| Dim. in mm               | а     | 162  | 165          | 167  | 209 | 209 | 208 |
|                          | b     | 60   | 68           | 76   | 82  | 82  | 89  |
|                          | h     | 83   | 92           | 98   | 100 | 100 | 108 |
|                          | у     | 14.5 | 16           | 16   | 22  | 22  | 22  |
|                          |       |      |              |      |     |     |     |
| Terminal for cond. cross |       | 1    | 1            | 1    | 2.5 | 2.5 | 2.5 |
| section (mm²) minmax.    |       | —2.5 | <b>—</b> 2.5 | —2.5 | —6  | —6  | 6   |
|                          |       |      |              |      | '   |     |     |