

Wall mounted receptacle  
Part no. 5785




- screw terminals
- switched
- mechanical DUO-interlock
- highly heat resistant contact carrier
- nickel plated contacts
- 3 pole switch
- receptacles can be padlocked

Technical specifications

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 16 A            |
| Poles                     | 7 p             |
| Voltage                   | 400 V           |
| Clock position            | 6 h             |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 67           |
| Enclosure material        | Plastic         |
| Weight                    | 1263 g          |
| Declaration of Conformity | EAC, CQC        |

Drawing



| Drawing                              | Amp.  | 16            | 32            |
|--------------------------------------|-------|---------------|---------------|
| 1 MB 382                             | Poles | 7             | 7             |
| Dim. in mm                           | a     | 225           | 225           |
|                                      | b     | 118           | 118           |
|                                      | c     | 147           | 153           |
|                                      | d     | 208           | 208           |
|                                      | e     | 101           | 101           |
|                                      | f     | 6.3           | 6.3           |
|                                      | g     | 8             | 8             |
|                                      | h     | 259           | 274           |
|                                      | M     | 1x25 and 1x32 | 1x25 and 1x32 |
|                                      | M*    | 2x25          | 2x25          |
| Max. cable diam. (mm)                |       | 25            | 25            |
| Terminal for cond. cross             |       | 1.5           | 2.5           |
| section (mm <sup>2</sup> ) min.-max. |       | —4            | —10           |