

**Plug**  
Part no. 677A




- screw terminals
- with cable gland

**Technical specifications**

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 32 A            |
| Poles                     | 3 p             |
| Voltage                   | 20-25, 40-50 V  |
| Clock position            | 4 h             |
| Hertz                     | 100-200 Hz      |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Weight                    | 177 g           |
| Declaration of Conformity | EAC, CQC        |

**Drawing**



| Drawing<br>2 MB 158                                              | Amp.<br>Poles | 16   |      | 32   |      |
|------------------------------------------------------------------|---------------|------|------|------|------|
|                                                                  |               | 2    | 3    | 2    | 3    |
| Dim. in mm                                                       | a             | 150  | 150  | 150  | 150  |
|                                                                  | b             | 55   | 55   | 55   | 55   |
|                                                                  | h             | 58   | 58   | 58   | 58   |
|                                                                  | m             | 128  | 128  | 128  | 128  |
|                                                                  | n             | 130  | 130  | 130  | 130  |
|                                                                  | y             | 24.7 | 24.7 | 24.7 | 24.7 |
| Terminal for cond. cross<br>section (mm <sup>2</sup> ) min.-max. |               | 4    | 4    | 4    | 4    |
|                                                                  |               | -10  | -10  | -10  | -10  |