

**Connector**  
Part no. 690A




- screw terminals
- with grommet

**Technical specifications**

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 16 A            |
| Poles                     | 3 p             |
| Voltage                   | 20-25, 40-50 V  |
| Clock position            | 4 h             |
| Hertz                     | 100-200 Hz      |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Weight                    | 205 g           |
| Declaration of Conformity | EAC, CQC        |

**Drawing**



| Drawing<br>3 MB 37                                  | Amp.<br>Poles | 16  |     | 32  |     |
|-----------------------------------------------------|---------------|-----|-----|-----|-----|
|                                                     |               | 2   | 3   | 2   | 3   |
| Dim. in mm                                          | a             | 144 | 144 | 144 | 144 |
|                                                     | b             | 55  | 55  | 55  | 55  |
|                                                     | h             | 67  | 67  | 67  | 67  |
|                                                     | m             | 122 | 122 | 122 | 122 |
|                                                     | y             | 25  | 25  | 25  | 25  |
|                                                     | z             | 9   | 9   | 9   | 9   |
| Terminal for cond. cross<br>section (mm²) min.-max. |               | 4   | 4   | 4   | 4   |
|                                                     |               | —10 | —10 | —10 | —10 |