

Wall mounted receptacle  
Part no. 7238




- screw terminals
- switched
- mechanical DUO-interlock
- circuit breaker, K-characteristics
- receptacles can be padlocked

Technical specifications

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 16 A            |
| Poles                     | 3 p             |
| Voltage                   | 230 V           |
| Clock position            | 6 h             |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 67           |
| Enclosure material        | Plastic         |
| Weight                    | 1950 g          |
| Declaration of Conformity | EAC, CQC        |

Drawing



|                          |       |       |       |       |       |       |      |      |
|--------------------------|-------|-------|-------|-------|-------|-------|------|------|
| Drawing                  | Amp.  | 16    |       |       | 32    |       | 63   |      |
| 1 MB 181/620             | Poles | 3     | 4     | 5     | 4     | 5     | 4    | 5    |
| Dim. in mm               | a     | 364   | 364   | 364   | 364   | 364   | 460  | 460  |
|                          | b     | 134   | 134   | 134   | 134   | 134   | 180  | 180  |
|                          | c     | 160   | 162   | 163   | 168   | 168   | 202  | 202  |
|                          | d     | 347   | 347   | 347   | 347   | 347   | 440  | 440  |
|                          | e     | 117   | 117   | 117   | 117   | 117   | 160  | 160  |
|                          | f     | 6.3   | 6.3   | 6.3   | 6.3   | 6.3   | 8.1  | 8.1  |
|                          | g     | 8     | 8     | 8     | 8     | 8     | 8    | 8    |
|                          | h     | 391   | 395   | 398   | 408   | 411   | 505  | 505  |
|                          | M     | 32/40 | 32/40 | 32/40 | 32/40 | 32/40 | 40   | 40   |
|                          | M*    | 2x32  | 2x32  | 2x32  | 2x32  | 2x32  | 2x40 | 2x40 |
| Max. cable diam. (mm)    |       | 27    | 27    | 27    | 27    | 27    | 27   | 27   |
| Terminal for cond. cross |       | 1.5   | 1.5   | 1.5   | 2.5   | 2.5   | 6    | 6    |
| section (mm²) min.-max.  |       | —4    | —4    | —4    | —10   | —10   | —25  | —25  |