

Connector StarTOP® with SafeCONTACT  
Part no. 731




- screwless, with insulation displacing technique
- cable gland and sealing
- strain relief and protection against kinking
- enclosure with thread lock and safety slide

Technical specifications

|                           |                         |
|---------------------------|-------------------------|
| Ampere                    | 32 A                    |
| Poles                     | 3 p                     |
| Voltage                   | 230 V                   |
| Clock position            | 6 h                     |
| Hertz                     | 50-60 Hz                |
| Connection technology     | Screwless - SafeCONTACT |
| Contact                   | standard                |
| Protection type           | IP 44                   |
| Weight                    | 328 g                   |
| Declaration of Conformity | VDE, EAC, CQC           |

Drawing



| Drawing<br>3 MB 60       | Amp.<br>Poles | 16   |      |      | 32  |     |     |
|--------------------------|---------------|------|------|------|-----|-----|-----|
|                          |               | 3    | 4    | 5    | 3   | 4   | 5   |
| Dim. in mm               | a             | 160  | 174  | 172  | 214 | 214 | 210 |
|                          | b             | 57   | 61   | 69   | 75  | 75  | 80  |
|                          | h             | 83   | 92   | 98   | 100 | 100 | 108 |
|                          | y             | 16   | 16   | 16   | 22  | 22  | 22  |
| Terminal for cond. cross |               | 1    | 1    | 1    | 2.5 | 2.5 | 2.5 |
| section (mm²) min.-max.  |               | —2.5 | —2.5 | —2.5 | —6  | —6  | —6  |