


Panel mounted inlet  
Part no. 837




- screw terminals
- nickel-plated contacts
- a retaining nose to hold the hinged lid of the connector must be provided by the customer in order to ensure satisfactory locking

Technical specifications

|                           |                        |
|---------------------------|------------------------|
| Ampere                    | 16 A                   |
| Poles                     | 4 p                    |
| Voltage                   | 230 V                  |
| Clock position            | 9 h                    |
| Hertz                     | 50-60 Hz               |
| Connection technology     | Screw terminals        |
| Contact                   | nickel plated contacts |
| Protection type           | IP 44                  |
| Weight                    | 157 g                  |
| Declaration of Conformity | EAC, CQC, VDE (ÜG)     |

Drawing



| Drawing<br>2 MB 173/2                | Amp.<br>Poles | 16   |      |      | 32   |      |      |
|--------------------------------------|---------------|------|------|------|------|------|------|
|                                      |               | 3    | 4    | 5    | 3    | 4    | 5    |
| Dim. in mm                           | a             | 85.7 | 85.7 | 85.7 | 85.7 | 85.7 | 85.7 |
|                                      | b             | 85.7 | 85.7 | 85.7 | 85.7 | 85.7 | 85.7 |
|                                      | c             | 72   | 72   | 72   | 90   | 90   | 90   |
|                                      | d             | 69.5 | 69.5 | 69.5 | 69.5 | 69.5 | 69.5 |
|                                      | e             | 69.5 | 69.5 | 69.5 | 69.5 | 69.5 | 69.5 |
|                                      | f             | 5.5  | 5.5  | 5.5  | 5.5  | 5.5  | 5.5  |
|                                      | g.            | 11   | 11   | 11   | 11   | 11   | 11   |
|                                      | g.1           | 2    | 2    | 2    | 2    | 2    | 2    |
|                                      | l             | 32   | 36   | 36   | 47   | 47   | 47   |
| Terminal for cond. cross             |               | 1.5  | 1.5  | 1.5  | 2.5  | 2.5  | 2.5  |
| section (mm <sup>2</sup> ) min.-max. |               | —4   | —4   | —4   | —10  | —10  | —10  |