

**AMAXX® receptacle combination**  
Part no. 900005




- pre-wired for installation
- hinged to the side
- enclosure and insert made of AMAPLAST
- fusing behind a transparent cover

Technical specifications

|                           |                                                                                                                                         |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| CEE 32 A, 5 p, 400 V DUO  | 2                                                                                                                                       |
| CEE 16 A, 5 p, 400 V DUO  | 2                                                                                                                                       |
| Fusing                    | <ul style="list-style-type: none"><li>• 1 RCD 63 A, 4 p, 0.03 A</li><li>• 2 MCB's 32 A, 3 p, C</li><li>• 2 MCB's 16 A, 3 p, C</li></ul> |
| Pre-fuse max.             | 63 A                                                                                                                                    |
| InA                       | 36 A                                                                                                                                    |
| RDF                       | 0.75                                                                                                                                    |
| Connection / feeder cable | <ul style="list-style-type: none"><li>• for 2 cables up to 5 x 25 mm²</li></ul>                                                         |
| Protection type           | IP 67                                                                                                                                   |
| Shutter                   | false                                                                                                                                   |
| Enclosure material        | Plastic                                                                                                                                 |
| Weight                    | 10500 g                                                                                                                                 |
| Height                    | 390 mm                                                                                                                                  |
| Width                     | 450 mm                                                                                                                                  |
| Declaration of Conformity | EAC                                                                                                                                     |

Drawing



Drawing 1 MB 522

Depth dimensions at various fittings.

| Receptacles       | Degrees | Depth  |
|-------------------|---------|--------|
| SCHUKO®16A, 230 V | IP 44   | 175 mm |
|                   | IP 67   | 194 mm |
| CEE 16A, 3p, 230V | IP 44   | 204 mm |
|                   | IP 67   | 205 mm |
| CEE 16A, 5p, 400V | IP 44   | 209 mm |
|                   | IP 67   | 213 mm |
| CEE 32A, 5p, 400V | IP 44   | 221 mm |
|                   | IP 67   | 227 mm |
| CEE 63A, 5p, 400V | IP 44   | 248 mm |
|                   | IP 67   | 248 mm |

Cable entries: closed for cut out. 2 x M 40 each on top and bottom, 2 x M 20 each on top and bottom for cut out.