


Wall mounted receptacle with TwinCONTACT
Part no. 9170




- screwless spring terminals
- highly resistant to chemicals
- suitable for through wiring
- with 2 external fixing points
- receptacles are designed for adding an auxiliary contact switch
- enclosure base can be turned 180°

Technical specifications

Ampere	32 A
Poles	4 p
Voltage	110 V
Clock position	4 h
Hertz	50-60 Hz
Connection technology	Screwless - TwinCONTACT
Contact	standard
Protection type	IP 67
Weight	498 g
Declaration of Conformity	EAC

Drawing



Drawing		16			32		
1 MB 622		Poles			Poles		
Dim. in mm		a	b	c	d	e	f
		100	100	100	100	100	100
		101	101	101	109	109	109
		117	125	131	157	157	160
		50	50	50	50	50	50
		84	84	84	92	92	92
		5.3	5.3	5.3	5.3	5.3	5.3
		5.3	5.3	5.3	5.3	5.3	5.3
		6.5	6.5	6.5	6.5	6.5	6.5
		131	131	132	148	148	148
		24.7	24.7	24.7	27.5	27.5	27.5
		25 (optional M20)			32 (optional M25)		
		2x25 (blind) to be cut out			2x25 (blind) to be cut out		
		18 (M25) and 15 (M20)			25 (M32) and 18 (M25)		
		1.5			2.5		
		—4			—6		
		—4			—6		
		—4			—6		

Max. cable diam. (mm)

Terminal for cond. cross

section (mm²) min.-max.