

**AMAXX® receptacle combination**  
Part no. 940006




- pre-wired for installation
- hinged to the side
- enclosure and insert made of AMAPLAST
- fusing behind a transparent cover

Technical specifications

|                           |                                                                                                                                                                    |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CEE 32 A, 5 p, 400 V      | 1                                                                                                                                                                  |
| CEE 16 A, 5 p, 400 V      | 1                                                                                                                                                                  |
| SCHUKO® 16 A, 230 V       | 3                                                                                                                                                                  |
| Fusing                    | <ul style="list-style-type: none"><li>• 1 RCD 63 A, 4 p, 0.03 A</li><li>• 1 MCB 32 A, 3 p, C</li><li>• 1 MCB 16 A, 3 p, C</li><li>• 3 MCB's 16 A, 1 p, C</li></ul> |
| Pre-fuse max.             | 100 A                                                                                                                                                              |
| InA                       | 45 A                                                                                                                                                               |
| RDF                       | 0.7                                                                                                                                                                |
| Connection / feeder cable | <ul style="list-style-type: none"><li>• for 2 cables up to 5 x 25 mm²</li></ul>                                                                                    |
| Protection type           | IP 44                                                                                                                                                              |
| Shutter                   | false                                                                                                                                                              |
| Enclosure material        | Plastic                                                                                                                                                            |
| Weight                    | 7320 g                                                                                                                                                             |
| Height                    | 520 mm                                                                                                                                                             |
| Width                     | 225 mm                                                                                                                                                             |

Drawing



Drawing 1 MB 523

Depth dimensions at various fittings.

| Receptacles        | Degrees | Depth  |
|--------------------|---------|--------|
| SCHUKO® 16A, 230 V | IP 44   | 186 mm |
|                    | IP 67   | 208 mm |
| CEE 16A, 3p, 230V  | IP 44   | 216 mm |
|                    | IP 67   | 220 mm |
| CEE 16A, 5p, 400V  | IP 44   | 222 mm |
|                    | IP 67   | 226 mm |
| CEE 32A, 5p, 400V  | IP 44   | 231 mm |
|                    | IP 67   | 236 mm |
| CEE 63A, 5p, 400V  | IP 44   | 260 mm |
|                    | IP 67   | 260 mm |

Cable entries: closed for cut out. 2 x M 40 each on top and bottom, 2 x M 20 each on top and bottom for cut out.