

Wall mounted receptacle

Part no. 1035



- screw terminals
- with highly heat resistant contact carrier
- nickel plated contacts
- internal fixing
- one cable entry at the top, two blind entries (can be cut out) at the bottom
- enclosure base can be turned 180°
- receptacles are designed for adding an auxiliary contact switch

Technical specifications

| | |
|---------------------------|---|
| Ampere | 16 A |
| Poles | 7 p |
| Voltage | 500 V |
| Clock position | 7 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | highly heat resistant contact carrier, nickel plated contacts |
| Protection type | IP 44 |
| Weight | 335 g |
| Declaration of Conformity | EAC, CQC |

Drawing



| Drawing | Amp. | 16 | 32 |
|------------|---|----------------------------|----------------------------|
| 1 MB 257 | Poles | 7 | 7 |
| Dim. in mm | a | 128 | 128 |
| | b | 84 | 84 |
| | c | 124 | 138 |
| | d | 11 | 11 |
| | e | 68 | 68 |
| | f | 5.3 | 5.3 |
| | g | 4 | 4 |
| | h | 145 | 160 |
| | M | 25 | 32 |
| | M* | 2x25 (blind) to be cut out | 2x25 (blind) to be cut out |
| | Max. cable diam. (mm) | 18 | 25 |
| | Terminal for cond. cross section (mm ²) min.-max. | 1.5 | 2.5 |
| | | —4 | —10 |