

Wall mounted receptacle  
Part no. 1418




- screw terminals
- internal fixing
- one cable entry at top, two blind cable entries (can be cut out) at bottom
- enclosure base can be turned 180°
- receptacles are designed for adding an auxiliary contact switch

Technical specifications

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 16 A            |
| Poles                     | 4 p             |
| Voltage                   | 400 V           |
| Clock position            | 6 h             |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Weight                    | 293 g           |
| Declaration of Conformity | VDE, EAC, CQC   |

Drawing



| Drawing<br>1 MB 43                               | Amp.<br>Poles | 16                         |         | 32                         |         |         |
|--------------------------------------------------|---------------|----------------------------|---------|----------------------------|---------|---------|
|                                                  |               | 4                          | 5       | 3                          | 4       | 5       |
| Dim. in mm                                       | a             | 128                        | 128     | 128                        | 128     | 128     |
|                                                  | b             | 84                         | 84      | 84                         | 84      | 84      |
|                                                  | c             | 122                        | 124     | 136                        | 136     | 138     |
|                                                  | d             | 11                         | 11      | 11                         | 11      | 11      |
|                                                  | e             | 68                         | 68      | 68                         | 68      | 68      |
|                                                  | f             | 5.3                        | 5.3     | 5.3                        | 5.3     | 5.3     |
|                                                  | g             | 4                          | 4       | 4                          | 4       | 4       |
|                                                  | h             | 144                        | 145     | 158                        | 158     | 160     |
|                                                  | M             | 25                         | 25      | 32                         | 32      | 32      |
|                                                  | M*            | 2x25 (blind) to be cut out |         | 2x25 (blind) to be cut out |         |         |
| Max. cable diam. (mm)                            |               | 18                         | 18      | 18/25                      | 18/25   | 18/25   |
| Terminal for cond. cross section (mm²) min.-max. |               | 1.5 1.5                    | 1.5 1.5 | 2.5 2.5                    | 2.5 2.5 | 2.5 2.5 |
|                                                  |               | —4 —4                      | —4 —4   | —10 —10                    | —10 —10 | —10 —10 |