

Connector PowerTOP® Xtra  
Part no. 14223



- screw terminals
- with rubberised grip area
- frame terminals
- X-CONTACT
- cable gland and sealing
- strain relief and protection against kinking
- enclosure with thread lock
- two safety slides
- products with pilot contact on request

Technical specifications

|                           |                                                   |
|---------------------------|---------------------------------------------------|
| Ampere                    | 125 A                                             |
| Poles                     | 5 p                                               |
| Voltage                   | 110 V                                             |
| Clock position            | 4 h                                               |
| Hertz                     | 50-60 Hz                                          |
| Connection technology     | Screw terminals                                   |
| Contact                   | highly heat resistant contact carrier, X-CONTACT® |
| Protection type           | IP 67                                             |
| Weight                    | 1514 g                                            |
| Declaration of Conformity | VDE, EAC                                          |

Drawing



| Drawing<br>3 MB 68       | Amp.<br>Poles | 63  |     |     | 125 |     |     |
|--------------------------|---------------|-----|-----|-----|-----|-----|-----|
|                          |               | 3   | 4   | 5   | 3   | 4   | 5   |
| Dim. in mm               | a             | 270 | 270 | 270 | 310 | 310 | 310 |
|                          | b             | 113 | 113 | 113 | 125 | 125 | 125 |
|                          | h             | 123 | 123 | 123 | 135 | 135 | 135 |
|                          | y             | 36  | 36  | 36  | 49  | 49  | 49  |
| Terminal for cond. cross |               | 6   | 6   | 6   | 25  | 25  | 25  |
| section (mm²) min.-max.  |               | —16 | —16 | —16 | —50 | —50 | —50 |