

Panel mounted receptacle
Part no. 1468



- screw terminals
- 20° inclination

Technical specifications

Ampere	16 A
Poles	4 p
Voltage	500 V
Clock position	7 h
Hertz	50-60 Hz
Connection technology	Screw terminals
Contact	standard
Protection type	IP 44
Flange	100x92 mm
Fixing hole	85x77 mm
Inclination	20 °
Weight	183 g
Declaration of Conformity	EAC, CQC

Drawing



Drawing		16			32		
1 MB 260		Amp.			Poles		
Dim. in mm		3	4	5	3	4	5
a	73.5	100	100	100	100	100	100
b	64	92	92	92	92	92	92
c	50	59	58	62	62	61	
d	60	85	85	85	85	85	
e	52	77	77	77	77	77	
f	5.5	5.5	5.5	5.5	5.5	5.5	
g	7	8	8	8	8	8	
g-1	2	2	2	2	2	2	
h	79	100	100	103	103	106	
k	44	34	34	54	54	49	
l	52	55	65	67	67	72	
l1	60	63	72	82	82	85	
α	20°	20°	20°	20°	20°	20°	
Terminal for cond. cross		1.5	1.5	1.5	2.5	2.5	2.5
section (mm²) min.-max.		—4	—4	—4	—10	—10	—10