

Panel mounted receptacle  
Part no. 1568




- screw terminals
- 20° inclination
- 32 A receptacles optional fitted with auxiliary contact

Technical specifications

|                       |                 |
|-----------------------|-----------------|
| Ampere                | 32 A            |
| Poles                 | 4 p             |
| Voltage               | 50-500 V        |
| Clock position        | 2 h             |
| Hertz                 | 300-500 Hz      |
| Connection technology | Screw terminals |
| Contact               | standard        |
| Protection type       | IP 67           |
| Flange                | 100x92 mm       |
| Fixing hole           | 85x77 mm        |
| Inclination           | 20 °            |
| Enclosure material    | Plastic         |

Drawing



| Drawing<br>1 MB 251 | Amp.<br>Poles                                       | 16        |           |           | 32         |            |            |
|---------------------|-----------------------------------------------------|-----------|-----------|-----------|------------|------------|------------|
|                     |                                                     | 3         | 4         | 5         | 3          | 4          | 5          |
| Dim. in mm          | a                                                   | 73.5      | 100       | 100       | 100        | 100        | 100        |
|                     | b                                                   | 64        | 92        | 92        | 92         | 92         | 92         |
|                     | c                                                   | 52        | 60        | 62        | 64         | 64         | 66         |
|                     | d                                                   | 60        | 85        | 85        | 85         | 85         | 85         |
|                     | e                                                   | 52        | 77        | 77        | 77         | 77         | 77         |
|                     | f                                                   | 5.5       | 5.5       | 5.5       | 5.5        | 5.5        | 5.5        |
|                     | g                                                   | 8         | 8         | 8         | 8          | 8          | 8          |
|                     | g.1                                                 | 2         | 2         | 2         | 2          | 2          | 2          |
|                     | h                                                   | 84        | 100       | 105       | 109        | 109        | 113        |
|                     | i                                                   | 78        | 85        | 96        | 103        | 103        | 110        |
|                     | k                                                   | 43        | 32        | 32        | 53         | 53         | 45         |
|                     | l                                                   | 52        | 55        | 65        | 67         | 67         | 72         |
|                     | lt                                                  | 60        | 63        | 72        | 82         | 82         | 85         |
|                     | o                                                   | 20°       | 20°       | 20°       | 20°        | 20°        | 20°        |
|                     | Terminal for cond. cross<br>section (mm²) min.-max. | 1.5<br>—4 | 1.5<br>—4 | 1.5<br>—4 | 2.5<br>—10 | 2.5<br>—10 | 2.5<br>—10 |