

**Panel mounted receptacle with TwinCONTACT**  
Part no. 1633




- screwless spring terminals
- suitable for through wiring
- 20° inclination
- 32 A receptacles are designed for adding an auxiliary contact switch

**Technical specifications**

|                           |                         |
|---------------------------|-------------------------|
| Ampere                    | 16 A                    |
| Poles                     | 3 p                     |
| Voltage                   | 400 V                   |
| Clock position            | 9 h                     |
| Hertz                     | 50-60 Hz                |
| Connection technology     | Screwless - TwinCONTACT |
| Contact                   | standard                |
| Protection type           | IP 44                   |
| Flange                    | 73.5x64 mm              |
| Fixing hole               | 60x52 mm                |
| Inclination               | 20 °                    |
| Weight                    | 120 g                   |
| Declaration of Conformity | VDE, EAC                |

**Drawing**



| Drawing<br>1 MB 465<br>Dim. in mm                   | Amp.<br>Poles | 16          |             |             | 32          |             |             |
|-----------------------------------------------------|---------------|-------------|-------------|-------------|-------------|-------------|-------------|
|                                                     |               | 3           | 4           | 5           | 3           | 4           | 5           |
| a                                                   |               | 73.5        | 100         | 100         | 100         | 100         | 100         |
| b                                                   |               | 64          | 92          | 92          | 92          | 92          | 92          |
| c                                                   |               | 52          | 58          | 58          | 61          | 61          | 60          |
| d                                                   |               | 60          | 85          | 85          | 85          | 85          | 85          |
| e                                                   |               | 52          | 77          | 77          | 77          | 77          | 77          |
| f                                                   |               | 5.5         | 5.5         | 5.5         | 5.5         | 5.5         | 5.5         |
| g                                                   |               | 7           | 8           | 8           | 8           | 8           | 8           |
| g.1                                                 |               | 2           | 2           | 2           | 2           | 2           | 2           |
| h                                                   |               | 79          | 100         | 100         | 103         | 103         | 105         |
| k                                                   |               | 31          | 31          | 31          | 44          | 44          | 54          |
| l                                                   |               | 52          | 55          | 65          | 70          | 70          | 73          |
| l1                                                  |               | 60          | 63          | 72          | 82          | 82          | 85          |
| Terminal for cond. cross<br>section (mm²) min.-max. |               | 1.5 1.5 1.5 | 2.5 2.5 2.5 | 2.5 2.5 2.5 | 2.5 2.5 2.5 | 2.5 2.5 2.5 | 2.5 2.5 2.5 |
|                                                     |               | -4 -4 -4    | -6 -6 -6    | -6 -6 -6    | -6 -6 -6    | -6 -6 -6    | -6 -6 -6    |